

ALL ALUMINIUM CEILING SPEAKER

DO3-51-3103-FP136TB-V230311

Page 1/1

DESCRIPTION

- Multipurpose high quality ceiling speakers.
- Ideal for music, speech and Emergency messages.
- Dual cones wide band silicon treated speaker.
- Suitable either for public areas or humid and steamed rooms.
- Impregnated low insertion loss multi-taps transformer.
- White RAL 9010 epoxy coated all aluminium grill and chassis.
- Tool free easy spring ceiling mounting.
- Ceramic fireproof connector (Optional)



Option : Dome



TECHNICAL SPECIFICATIONS

Nominal Power (100V)	Watts	6
Maximum Power	Watts	10
Frequency response	Hertz	150-20000
SPL (max) 1W@1m	dB	88-(96)
Connection	Terminals	
Power Taps (100V)	Watts	6/3/1,5
Impédances	Ohms	1,7/3,3/6,7K
Pack dimensions : WxHxD	mm	135x135x150
Pack Weight	Kg	0,9

CONFIGURATION

	1	2	3	
50V	1,5	0,7	0,4	WATTS
70V	3	1,5	0,7	
100V	6	3	1,5	

Transformer T 1200

Push connector

DIMENSIONS

OPTION : DOME

Standard mounting frame

30 mm

Fixing hole 110 mm

85 mm

98 mm

130 mm

Push connector

92 mm Conical dome

With One cable gland

103 mm

97 mm

118 mm Fixing hole

112 mm

130 mm High with cable gland

SPECIFICATIONS SUBJECT TO MODIFICATIONS

DOCUMENT NON CONTRACTUEL



MERLAUD

9 rue de La Briqueterie - P.A.E. des FAUVETTES - 95330 DOMONT (FRANCE)
 Tel. 01 39 91 77 78 - Fax 01 39 91 90 66 - www.merlaud.com - merlaud@merlaud.com